

Seaglaze can take no responsibility for which specific products should be used, however we have received a variety of feedback from customer so can offer some guidance.

If required Installation and Spares Kits are available from Seaglaze. Please contact us for details.

Warnings:

- Only use warm soapy water to clean any of our products. Do not use products such as acetone or bleach etc.
- If any metal products come into contact with salt water we would always recommend that they are rinsed with fresh, clean water to remove any salt deposits that will build up and will accelerate corrosion.
- Wire wool should not be used on any Seaglaze products.
- Only Marine grade screws of the correct length should be used.
- If your window is glazed with Toughened Safety Glass it is important not to use knives or screw drivers around the glass as this could cause the pane to shatter.
- If the window is glazed with Acrylic please note that it is easily scratched by tools and scratches can not be removed.

For **LAMINATE GLASS Windows** it is important that no chemical, cleaning products or non silicone based products come into contact with the edge of the glass (including sikaflex 296). If these products come into contact with the edge of the glass this can cause irreversible damage to the interlayer.

Laminate windows should be backfilled with Sikasil WS-605-S ONLY. Certain other commonly used solvents and adhesives can permanently damage the interlayer.

P.T.O

Seaglaze can not offer guidance on how these products should be used, the manufactures directions should always be followed. Details and Data Sheets can be found at www.gbr.sika.com

Framed Windows:

Seaglaze would always recommend a non adhesive product should be used to hold windows with a frame in place while fixing. A non adhesive mastic is recommended for simplicity and for ease of removing the windows if required in later years.

A variety of Seaglaze customer have has positive results using products such as...

- Sikasil WS-605-S—High Performing Weatherproofing Sealant
Backfill—After fitting Sikasil WS-605-S can be used to backfill if required.

Direct Bond Glass Windows Only:

Direct Bond windows are the only product where an adhesive should be used.

A variety of Seaglaze customer have has positive results using products such as...

- Sikaflex-296—Marine Window Adhesive

Backfill—After 24hrs Sikasil WS-605-S can be used to back fill. A minimum of 24hrs must be left after bonding the glass to ensure the adhesive product has cured properly.

Direct Bond Plastic Windows Only:

Direct Bond windows are the only product where an adhesive should be used. An Activator should not be used on and form of plastic when bonding, this will cause a milky sheen on the plastic.

A variety of Seaglaze customer have has positive results using products such as...

- Sikaflex-295—Marine Window Adhesive (for plastics)

Backfill—After 24hrs Sikasil WS-605-S can be used to back fill. A minimum of 24hrs must be left after bonding the glass to ensure the adhesive product has cured properly.

END OF INSTRUCTION

Seaglaze can not offer guidance on how these products should be used, the manufactures directions should always be followed. Details and Data Sheets can be found at www.gbr.sika.com